

0

(e)

Product Information

DCD-50





DCD-50

CD PLAYER

HIGH QUALITY CD PLAYER WITH APPEALING DESIGN AND COMPACT SIZE

Real Hi-Fi for today's lifestyles. Best matching with the PMA-50 Denon Design Series Stereo Amplifier, the new DCD-50 now sees the light of day. Denon's engineers used their extensive expertise to create a full digital Hi-Fi series with the company's renowned sonic quality, and put

it into a compact size. The DCD-50 owns an elegant slot-in CD drive, ready for regular audio CDs and MP3/WMA files on a disc alike. Most remarkably, the DCD-50 allows full digital signal processing from DCD to PMA, for pure, unadulterated playback of beloved CD collections.



Denon Design Series - Hi-Fi for today's lifestyles

Featuring the same high quality styling and finish, the DCD-50 is the perfect partner for the PMA-50 digital integrated amplifier. The compact chassis features deluxe finishes including soft aluminum matte with bright silver tone accents and glossy and matte black surfaces.

Versatile Disc Playback

The DCD-50 plays music CDs and can also play data CDs, including CD-R and CD-RW discs with MP3 and WAV audio tracks.

Vertical or Horizontal Placement

When desktop or shelf space is at a premium, the DCD-50 can be vertically positioned alongside or above the PMA-50. The 4 feet are easily removable by hand, and the chassis side features caps covering 4 screw holes. Simply remove the existing caps and screw in the feet. Then, put the supplied 4 silver caps into the original bottom screw holes and you're all set.

Ergonomic Remote Control

The supplied remote control features an ergonomically-designed layout that includes a cursor keypad, number keypad and dedicated function buttons such as random, repeat, info and program. You can control both DCD-50 and PMA-50 with a supplied single

Clear View OLED Display with Dimmer

The OLED display shows the CD's total tracks and total time, as well as the track number and track time, and the song title, artist name and album name (depending on the disc), along with icons for random mode, repeat 1 and repeat all modes, and a folder icon for data discs.

The display automatically rotates to match the installation orien-

The dimmer function features 3 levels of display brightness, adjustable via the remote control. When paired with the PMA-50, you can adjust the display brightness of both units at the same time.

High Resolution D/A Conversion

For optimum audio quality with the PMA-50, the DCD-50 is equipped with a coaxial digital audio output - for an easy setup the required digital audio coax cable is included. For connection to other audio components that do not have a digital coaxial input, the DCD-50 features a high quality D/A con-version block with 32-bit/192-kHz D/A converter that delivers wide dynamic range, along with extremely low noise and distortion.

Selectable Auto Play

If you prefer, you can easily configure via the remote control the DCD-50 to wakeup from standby and start immediate playback when you insert a disc. Once configured, the DCD-50 will retain your preferred mode until you decide to change it.

Automatic Standby Option

You also have the ability to activate the Auto Standby function, which will automatically put the DCD-50 in standby mode after 30 minutes of inactivity, saving energy and the environment.

KEY FEATURES

- High quality CD Transporter/Player, best matching with Denon PMA-50
- Slot-in CD mechanism, supporting CD audio and MP3/WMA discs
- · Digital Coaxial output

STATE-OF-THE-ART DENON SOLUTIONS FOR MAXIMISING CONTENT QUALITY

- 32 bit/192kHz D/A converter with analogue output (RCA)
- High-grade audio components

EASE-OF-USE AND OTHER FEATURES

- Horizontal or vertical placement with rotating display
- Easy-to-use remote control
- . Auto Standby and low power consumption at stand-by 0.4 W







DCD50SPF2 4951035056110 Premium Silver EAN DCD50SPE2GB 4951035056110 Premium Silver

Ports		
OUT	Analogue out (cinch)	x 1
	Digital Coaxial out	x 1

Other trademarks and trade names are those of their respective owners. nark of D&M Holdings, Inc

- All specs can be subject to change
- * Available in Premium Silve

Technical information CD section

Channels Dynamic range Signal-to-noise ratio

Total harmonic distortion

2 channel stereo 100 dB 105 dB 0.004% (1 kHz)

Power supply Power consumption Dimensions (W x H x D)

General

AC 230 V, 50/60kHz 10 W (Standby 0.4 W) 200 x 86 x 240mm 2.4 kg

|V01|